

- 1 -

# TITLE OF THE INVENTION

METHOD AND APPARATUS FOR EXECUTING PLURAL  
PROCESSES ON A MICROELECTRONIC WORKPIECE AT A SINGLE  
PROCESSING STATION

## CROSS-REFERENCE TO RELATED APPLICATIONS

Not Applicable

## STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable

## BACKGROUND OF THE INVENTION

The fabrication of microelectronic components from a workpiece, such as a semiconductor wafer substrate, polymer substrate, etc., involves a substantial number of processes. There are a number of different processing operations performed on the workpiece to fabricate the microelectronic component(s). Such operations include, for example, material deposition, patterning, doping, chemical mechanical polishing, electropolishing, and heat treatment.

Material deposition processing involves depositing thin layers of electronic material to the surface of the workpiece (hereinafter described as, but not limited to, a semiconductor wafer). Patterning provides removal of selected portions of these added layers. Doping of the semiconductor wafer is the process of adding impurities known as "dopants" to the selected portions of the wafer to

- 2 -

alter the electrical characteristics of the substrate material. Heat treatment of the semiconductor wafer involves heating and/or cooling the wafer to achieve specific process results. Chemical mechanical polishing involves the removal of material through a combined chemical/mechanical process while electropolishing involves the removal of material from a workpiece surface using electrochemical reactions.

Numerous processing devices, known as processing "tools", have been developed to implement the foregoing processing operations. These tools take on different configurations depending on the type of workpiece used in the fabrication process and the process or processes executed by the tool. One tool configuration, known as the Equinox(R) wet processing tool and available from Semitool, Inc., of Kalispell, Montana, includes one or more workpiece processing stations that utilize a workpiece holder and a process bowl or container for implementing wet processing operations. Such wet processing operations include electroplating, etching, cleaning, electroless deposition, electropolishing, etc.

In accordance with one configuration of the foregoing Equinox(R) tool, the workpiece holder and the process bowl are disposed proximate one another and function to bring the semiconductor wafer held by the workpiece holder into contact with a processing fluid disposed in the process bowl and forming a processing chamber.

Conventional workpiece processors have utilized various techniques to bring the processing fluid into contact with the surface of the workpiece in a

- 3 -

controlled manner. For example, the processing fluid may be brought into contact with the surface of the workpiece using a controlled spray. In other types of processes, such as in partial or full immersion processing, the processing fluid resides in a bath and at least one surface of the workpiece is brought into contact with or below the surface of the processing fluid.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210

- 4 -

## BRIEF SUMMARY OF THE INVENTION

An apparatus for processing a microelectronic workpiece is set forth. The apparatus comprises a workpiece support adapted to hold the microelectronic workpiece and a processing container adapted to receive the microelectronic workpiece held by the workpiece support. A drive mechanism is connected to drive the processing container and the workpiece support holding the microelectronic workpiece relative to one another so that the microelectronic workpiece may be moved to a plurality of workpiece processing positions. At least two chemical delivery systems are employed. A first chemical delivery system is used to provide at least one processing fluid to the processing container for application to the microelectronic workpiece when the microelectronic workpiece is in a first one of the plurality of workpiece processing positions while a second chemical delivery system is used to provide at least one processing fluid to the processing container for application to the microelectronic workpiece when the microelectronic workpiece is in a second one of the plurality of microelectronic workpiece processing positions. The apparatus also includes at least two chemical collector systems. A first chemical collector system is used to assist in at least partially removing spent processing fluid provided by the first chemical delivery system while the microelectronic workpiece is in the first one of the plurality of workpiece processing positions. Similarly, a second chemical collector system is used to assist in at least partially removing spent processing fluid provided by the second chemical delivery system from the processing

Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

- 6 -

## BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIGURE 1 is a perspective view of a reactor constructed in accordance with one embodiment of the present invention.

FIGURE 2 is a cross-sectional view of the reactor illustrated in FIGURE 1.

FIGURE 3 is a further cross-sectional view of the reactor illustrated in FIGURE 1.

FIGURES 4 and 5 illustrate the orientation of the processing head and corresponding workpiece during a workpiece loading operation.

FIGURES 6 – 9 are cross-sectional views of the reactor of FIGURE 1 illustrating the microelectronic workpiece at various processing positions within the processing container.

FIGURES 10 and 11 are cross-sectional views of the reactor of FIGURE 1 illustrating the microelectronic workpiece at various angular positions within the second processing portion of the processing container so as to vary the position of initial contact of a stream of processing fluid with a surface of the microelectronic workpiece.

- 7 -

## DETAILED DESCRIPTION OF THE INVENTION

With reference to FIGURES 1 -3, there is shown a reactor assembly 20 for processing a microelectronic workpiece, such as a semiconductor wafer 25 or the like. Generally stated, the reactor assembly 20 is comprised of a reactor head, shown generally at 30, that includes one or more components used to support the workpiece 25. Additionally, the reactor assembly 20 includes a corresponding reactor container, shown generally at 35, that receives one or more processing fluids from one or more chemical delivery systems.

The reactor head 30 of the reactor 20 is preferably comprised of a stationary assembly 40 and, optionally, a rotor assembly 45 that is driven by a corresponding rotor motor 47. Rotor assembly 45 may be configured to receive and carry an associated wafer 25 or like workpiece, position the workpiece in a process-side down orientation within reactor container 35, and to rotate or spin the workpiece. The rotor assembly 45 and/or reactor head 30 may also be used to elevate the workpiece after initial contact with a processing liquid so that only a meniscus of the processing fluid contacts the side of the workpiece that is to be processed. This also falls within the ambit of an immersion process.

The reactor head 30 is mounted on a lift/rotate apparatus 50 which is configured to rotate the reactor head 30 from an upwardly-facing disposition in which it receives the wafer to be plated, to a downwardly facing disposition in which the surface of the wafer to be processed is positioned so that it may be brought into contact with a processing fluid, such as an electroplating solution, in

- 8 -

reactor container 35. A robotic arm (not illustrated), which may include an end effector, is typically employed for placing the workpiece 25 in position on the rotor assembly 45, and for removing the processed wafer from within the rotor assembly 45 after processing is complete.

Lift/rotate apparatus 50 is preferably capable of moving the workpiece 25 to a plurality of positions with respect to reactor container 35. More particularly, the lift/rotate apparatus 50 may be capable of moving the reactor head 30 and the corresponding workpiece 25 in a vertical fashion toward and away from the reactor container 35. Such vertical motion may be directed by a programmable control system 55 or the like. Programmable control system 55 may also be used to adjust the spin rate of the rotor motor 47.

Although lift/rotate apparatus 50 of the disclosed embodiment has the ability to rotate reactor head 30 for presentation of the workpiece 25 by a corresponding robot in a process-side up orientation, it will be recognized that apparatus 50 need not have such rotation abilities. Rather, the workpiece 25 may be presented to the reactor head 30 by the corresponding robot in a process-side down orientation. In such instances, rotation of the workpiece to the process-side down orientation may take place on the corresponding robot or another apparatus within the overall processing system.

The reactor container 35 includes a first processing portion, shown generally at 60, that is configured to execute a first process in which one or more processing fluids are delivered to treat at least one surface of the workpiece 25. In



- 9 -

the illustrated embodiment, for exemplary purposes, first processing portion 60 of container 35 is configured to execute an electroplating process. However, the first processing portion 60 of container 35 may be alternatively configured to execute any number of different processes. Such processes include, but are not limited to, immersion processes, vapor processes, spray processes, gaseous processes, etc.

Pursuant to executing an electroplating process in the first processing portion 60, container 35 is configured to provide a flow of an electroplating solution to one or more surfaces of the workpiece 25. To this end, container 35 includes an interior container 65 having an inlet 70 through which a flow of electroplating solution is provided. The electroplating solution provided through inlet 70 flows through the interior container 65 and overflows therefrom about an upper weir 75 into an exterior overflow region 77. This type of reactor assembly is particularly suited for effecting electroplating of semiconductor wafers or like workpieces, in which an electrically conductive, thin-film layer of the wafer is electroplated with a blanket or patterned metallic layer while in a process-side down orientation.

Within the interior container 65 there is an anode assembly, shown generally at 80, having one or more anodes 85 that is in the electrical contact with the electroplating solution (although the illustrated embodiment utilizes a single anode 85). The one or more anodes 85 are electrically connected to a source of electroplating power (not shown) through one or more electric conductive structures. The anode assembly 80 may be constructed in the manner set forth in

- 10 -

PCT Application No. PCT/US99/15430, entitled "REACTOR VESSEL HAVING IMPROVED CUP, ANODE AND CONDUCTOR ASSEMBLY", filed July 9, 1999 (Attorney Docket No. SEM4492P0200PC; Corporate Docket No. P98-0017PCT), the teachings of which are hereby incorporated by reference.

An alternative reactor container suitable for immersion processing is set forth in U.S.S.N. 60/143,769, entitled "workpiece processor having improved processing chamber", filed July 12, 1999 (Attorney Docket No. SEM4492P0831US; Corporate Docket No. P99-0034 ).

In those instances in which the reactor is to be used in an electroplating process, the rotor assembly 45 of head 30 may include one or more cathode contacts that provide electroplating power to the surface of the wafer. In the illustrated embodiment, a cathode contact assembly is shown generally at 90. This cathode contact assembly may be constructed in accordance with the teachings of PCT Application No. PCT/US99/15847, entitled "METHOD AND APPARATUS FOR COPPER PLATING USING ELECTROLESS PLATING AND ELECTROPLATING", filed July 12, 1999 (Attorney Docket No. SEM4492P0571PC; Corporate Docket No. P99-0025PCT). Although the various contact configurations illustrated in that patent application provide electroplating power directly to the side of the wafer that is to be processed, it will be recognized that backside contact may be implemented in lieu of front side contact when the substrate is conductive or other means are provided to electrically connect the backside of the workpiece with the process side thereof. The contact

- 11 -

assembly 90 may be operated between an open state that allows the wafer to be placed on the rotor assembly 45, and a closed state that secures the wafer to the rotor assembly and brings the electrically conductive components of the contact assembly 85 into electrical engagement with the surface of the wafer that is to be plated.

Processing container 35 also includes a second processing portion, shown generally at 95, that is adapted to execute a further process on one or more surfaces of the microelectronic workpiece 25. In the illustrated embodiment, the second processing portion 95 is adapted to execute a process in which a processing fluid is provided at the downward facing surface of the workpiece 25. To this end, one or more nozzles 100 are provided in the second processing portion 95 and are directed toward the workpiece 25.

It is often desirable to at least partially inhibit mixing of the processing chemicals used in different processing steps. Reactor container 35 therefore includes separate collection systems for collecting spent processing fluids (e.g., processing fluids that have contacted one or more surfaces of the workpiece 25). With respect to the illustrated embodiment, the processing fluids used in processes carried out in the first processing portion 60 of reactor container 35 are liquids that overflow the weir 75 of the interior container 65 and enter the overflow region 77. After entering the overflow region 77, the processing chemicals are removed through one or more outlets that are in fluid

- 12 -

communication with the overflow region 77. The fluid exiting from the reactor container 35 subsequently undergoes disposal, recycling, constituent dosing, etc.

In those instances in which the processing fluid used in the first processing portion 60 is in a gaseous or vapor state, overflow region 77 may be connected to a vacuum source. Spent processing fluid may then be removed as it overflows the weir 75. As above, process fluid exiting from the reactor container 35 may subsequently undergo disposal, recycling, constituent dosing, etc..

A further collection system is used for collecting spent processing fluids employed in processes carried out in the second processing portion 95. The further collection system, generally designated at 105, is provided in or proximate the second processing portion 95. In the illustrated embodiment, the first processing portion 60 of reactor container 35 is disposed vertically below the second processing portion 95 and, further, is open to the second processing portion 95. These factors complicate the collection process as it is to be executed by the further collection system. For example, if a liquid is used as the processing fluid in the second processing portion 95 and delivered to a surface of the microelectronic workpiece 25, liquid drops can readily enter and adversely effect the first processing portion 60. Although small amounts of the liquid may be tolerated in the first processing portion 60, the substantial amounts of the liquid that are often introduced during spray processing or like can and often will reduce the effectiveness of the processing that takes place in the first processing portion 60.

- 13 -

To overcome the foregoing problems, the further collection system 105 is in the form of one or more fluid channels, shown generally at 110, that are disposed at the inner periphery of reactor container 35. As shown, the fluid channels 110 are located in the second processing portion 95 proximate the position of the workpiece 25 as it undergoes processing in the second processing portion 95. Each fluid channel, as illustrated in FIGURES 2 and 3, may be defined by a splash wall 115 and a retainer wall 120. The splash wall 115 and retainer wall 120 may each be disposed at an angle with respect to horizontal. The manner in which this further collection system functions will become clearer in connection with the operational description below.

In operation, the reactor head 30 is elevated and rotated by the lift/rotate apparatus 50 to a loading position, illustrated in FIGURE 4, that is located above the reactor container 35. While in this position, a workpiece 25 is placed upon rotor assembly 45 with the side of the workpiece that is to be electroplated facing upward. The contact assembly 90 of the rotor assembly 45 is then actuated to grip the workpiece 25 and secure it therewith. This actuation also causes the contact assembly 90 to make electrical contact with the workpiece 25 to supply power for the electroplating operation. As noted above, however, rotation of the reactor head 30 need not take place in apparatus in which the workpiece 25 is rotated to a process-side down position prior to introduction of the workpiece 25 to the rotor assembly 45.

- 14 -

Once the workpiece 25 has been secured with the rotor assembly 45, the lift/rotate apparatus 50 is directed by the control system 55 to rotate the reactor head 30 so that the surface of the workpiece that is to be processed is faced downward, as illustrated in FIGURE 5 . With the workpiece 25 in this state, the control system 55 directs the lift/rotate apparatus 50 to drive the rotor assembly 45 and the corresponding workpiece to a first workpiece processing position within the reactor container 35. This first workpiece processing position may be located in either the first processing portion 60 or the second processing portion 95 of the reactor container 35. For exemplary purposes, it will be assumed that processing will first take place in the first processing portion 60. As such, the lift/rotate apparatus 50 is directed by the control system 55 to take the necessary steps to bring the workpiece 25 to the position illustrated in FIGURE 6. In this position, at least the lower surface of the workpiece 25 is brought into contact with a flow of electroplating solution provided at the upper portion of interior container 65. Electroplating power is then provided to both the workpiece 25 and the anode 85 to affect electroplating of the surface. During the electroplating process, spent processing fluid is collected within the overflow region 77 and removed from the reactor container 35.

Once electroplating is completed in the first processing portion 60, the control system 55 directs the lift/rotate apparatus 50 to move the workpiece 25 to an intermediate position, designated generally at 57 of FIGURE 7. While at this position, the workpiece 25 is spun at a high rotation rate to fling off a bulk

- 15 -

portion of any excess electroplating solution. This reduces drag out and waste of the electroplating solution.

After the bulk portion of the excess electroplating solution has been flung off, the control system 55 directs the lift/rotate apparatus 50 to move the workpiece 25 to a second processing position. Here, in the exemplary process, the second processing position is located in the second processing portion 95 of the reactor container 35. The lift/rotate apparatus 50 thus drives the workpiece 25 to the position illustrated in FIGURE 7. In this position, one or more further processing chemicals are provided from a chemical supply system to contact one or more surfaces of the workpiece 25. With respect to the specific embodiment disclosed herein, a liquid stream of a processing fluid, such as water that may or may not include additives, is provided through the one or more nozzles 100 to contact the lower surface of the workpiece 25 that has been electroplated. As the liquid stream is directed toward the workpiece surface, the rotor assembly 45 and corresponding workpiece 25 are rotated at a high rotation rate so that the liquid impinging on the workpiece surface is flung radially outward therefrom under the influence of centripetal acceleration. The liquid flung in this manner is collected by the further collection system 105. More particularly, the liquid flung in this manner contacts the splash wall 115 corresponding to the channel 110 that is immediately adjacent the lower surface of the workpiece 25, and proceeds downward therealong into the corresponding channel 110. Retainer wall 120, being disposed at an angle with respect to horizontal, assists in retaining the

- 16 -

accumulated liquid within the corresponding channel 110. One or more outlets 125 are placed in fluid communication with the channel 110 to allow the spent processing liquid to be removed from the reactor container 35. As such, the spent processing liquid used in the second processing portion 95 is effectively removed from the reactor container 35 by the further collection system 105, thereby minimizing the amount of the spent liquid that enters the first processing portion 60.

As can be seen in the FIGURES, a plurality of collection channels 110 may be used. In accordance with one embodiment of the present invention, all of the plurality of collection channels 110 can be connected to a common drain. Such a configuration is particularly useful in those instances in which a single processing fluid is employed for processing the workpiece when it is in the second processing portion 95. However, it may be desirable to process the workpiece 25 using more than one type of processing fluid in the second processing portion 95 while collecting the processing fluids separately. To this end, programmable control system 55 directs the lift/rotate apparatus 50 to a plurality of positions within the second processing portion 95. Here, those positions differ with respect to their vertical position within the reactor container 35.

A unique manner of delivering a fluid stream to the surface of a workpiece is illustrated in connection with FIGURES 7-9. As illustrated, the workpiece 25 is moved to a plurality of processing positions within the second



- 17 -

processing portion 95. With reference to FIGURE 7, the reactor head 30 is driven by the control system 55 to place the workpiece 25 at a first processing position within the second processing portion 95. In this position, nozzle 100 directs a stream of processing fluid 130 toward a central portion of the lower surface of the workpiece 25 at an upward angle. As the stream of processing fluid 130 is provided to the surface of workpiece 25, the control system 55 directs the reactor head 30 to move the workpiece 25 sequentially through the positions illustrated in FIGURES 7 through 9. Such movement through these positions can be executed in accordance with a controlled continuous velocity, a controlled velocity profile, or in discrete steps. As the workpiece 25 is moved to these various processing positions, the stream of processing fluid 130 from nozzle 100 is directed at a substantially fixed point in space. Since the stream 130 is fixed at an acute angle as the workpiece 25 is moved, the radial position at which the stream 130 contacts the workpiece 25 changes and approaches the periphery of the surface of workpiece 25. This is particularly useful when this apparatus configuration and method of operation are used in connection with electroplating operations, since the stream 130 may be comprised of deionized water and effectively "chase off" electroplating solution from surface of microelectronic workpiece 25.

As can be seen in the foregoing figures, a plurality of channels 110 are employed. Each channel 110 corresponds to one or more processing positions assumed by the workpiece 25 as it is processed in the second processing portion

- 18 -

95. In those instances in which a single processing fluid is used in the second processing portion 95, the channels 110 may be connected together and tied to a single outlet 135. However, it is also possible to provide different processing fluids to the surface of the workpiece 25 at different processing positions within the second processing portion 95. In such operations, channels 110 may be used to separately collect each of the processing fluids and provide them to separate outlets.

An alternative method (or additional method, if used in conjunction with the method described above) of delivering a stream of processing fluid to the downward facing surface of the workpiece 25 is illustrated in FIGURES 10 and 11. In accordance with this latter method, reactor head 30 is driven to a fixed position within second processing portion 95 by the lift/rotate apparatus 50 under the direction of control system 55. A stream of processing fluid is provided through one or more nozzles 100. Control system 55 directs lift/rotate apparatus 50 to rotate reactor head 30 through a plurality of angles so that the stream of processing fluid 130 makes initial contact with the lower surface of workpiece 25 at a plurality of portions thereof sequentially as a function of time. Again, workpiece 25 may be spun at a high rotation rate to fling off spent processing fluid into the fluid channels 110 of the further collection system 105 as the stream of processing fluid 130 is delivered to the surface of workpiece 25. Rotation of the reactor head 30 and corresponding workpiece 25 may be executed in accordance with a controlled motion profile, such as a controlled continuous or

- 19 -

variable rotation rate, between the starting and ending angular positions. Alternatively, the controlled motion profile may be in the form of discrete angular steps between the starting and ending angular positions.

FIGURES 10 and 11 illustrate starting and ending angular positions that may be employed, with FIGURE 10 illustrating the starting angular position and FIGURE 11 illustrating the ending angular position. In this illustrated embodiment, the stream of processing fluid 130 is initially directed to a central portion of the workpiece 25 as in FIGURE 10. Reactor head 30 and the corresponding workpiece 25 are then rotated through one or more angular positions to reach the ending angular position shown in FIGURE 11 in which the stream of processing fluid 130 is directed for initial contact with a peripheral portion of the workpiece 25.

Although, as noted above, the present invention is suitable for use in a wide range of microelectronic workpiece processes, it is particularly well-suited for use in microelectronic workpiece electroplating. After plating a wafer, the surface of the wafer that has been exposed to the plating solution is wetted with plating solution. The contact assembly and corresponding barrier seal are also wetted at the seal interface with the wafer. This condition is difficult to solve due to conflicting requirements. The wafer needs to remain wetted until the plating solution can be neutralized by deionized water or another neutralizer. The contact seal, on the other hand, needs the residual solution removed or dried to prevent migration of the plating solution to the sealed area, and ultimately behind

- 20 -

it, during product removal. Simply trying this residual plating solution is not an option to to the corrosive/oxidizing effect drying has on the plated film. Such problems are addressed by rinsing the wafer and seal interface before the wafer is removed from the reactor. Also, it has been found to be desirable to occasionally rinse the seal and electrical contact in the absence of a wafer to assist in preventing a buildup of copper salts.

Numerous modifications may be made to the foregoing system without departing from the basic teachings thereof. Although the present invention has been described in substantial detail with reference to one or more specific embodiments, those of skill in the art will recognize that changes may be made thereto without departing from the scope and spirit of the invention as set forth in the appended claims.